



www.cobrausa.com

Items Supplied >

- 1 Left Floor Board Assembly
- 1 Right Floor Board Assembly
- 2 Extension Plate
- 2 8mm x 20mm Bolt
- 4 8mm x 16mm Bolt
- 2 8mm Flange Nut

Application(s) >

Suzuki Boulevard M109R 06-14

Instruction Manual >

06-3845 / 06-4845

Page 1 of 1

Your Floorboards will install in just a few minutes using common tools. Read all instructions carefully and completely before installing your new Floorboards.

Left Side

- Remove seat
- 2. Remove lower side body panel from three(3) attachment grommets.
- 3. Remove two bolts retaining stock foot peg assembly.
- 4. Bolt on Cobra extension plate using two(2) stock bolts and one(1) each of supplied 8mm x 20mm bolt and flanged nut. *Torque to factory specifications*.
- 5. Replace body panel.
- 6. Bolt the Cobra floorboard to the extension plate using the two(2) supplied 8mm x 16mm w/loctite bolts. *Torque to 20 ft lbs or 28 Nm.*

Right Side

- 1. Remove allen screw from side body panel.
- Remove plastic rivet from top body panel and pull free from rear retaining grommet.
- 3. Remove lower side body panel from two(2) attachment grommets.
- 4. Bolt on Cobra extension plate using two(2) stock bolts and one(1) each of the supplied 8mm x 20mm bolt and flanged nut. *Torque to factory specifications*.
- Replace lower side body panel and allen bolt.
- 6. Push top body panel back onto retaining grommet and reinstall plastic rivet.
- 7. Bolt the Cobra floorboard to the extension plate using the two(2) supplied 8mm x 16mm w/loctite bolts. *Torque to 20 ft lbs or 28 Nm.*
- 8. Reinstall seat.

^{*} Cobra® recommends you always wear a helmet while riding. Please never operate your motorcycle while under the influence of alcohol and/or drugs. Enjoy the new look of your motorcycle and please ride safely.