COBRA

23801 E. La Palma Ave., Yorba Linda, CA 92887 Ph. 714.692.8180 Fax. 714.692.5016

www.cobrausa-vtwin.com Items Supplied > Application(s) > HARLEY 1 – FREEWAY BAR 2 - BOLT, BUTTONHEAD 3/8"-16 X 1" ALL FLST MODELS 2000-2017 2 - NUT, NYLOCK 3/8"-16 2 - 3/8" FLAT WASHER (Except FLSTC and FLSTS) 1 - BOLT, BUTTONHEAD 5/16-18 X 3/4" 1 - NUT, NYLOCK 5/16-18 1 – 5/16 FLAT WASHER Page 1 of 1 Instruction Manual > 601-2100B Read all instructions carefully before installing your new Cobra® product! Remove any accessories that may prohibit the installation of your new freeway bar. 1. Position the freeway bar into place between the frame rails and front tire. Align the holes in the freeway bar's 2. lower mounts with the open holes on the floorboard frame mounts. Insert the (2) supplied 3/8"-16 x 1" buttonhead bolts thru floorboard frame mounts and lower freeway bar mounts; secure with supplied 3/8" flat washers and nylock nuts. See Diagrams. DO NOT FULLY TIGHTEN. Rotate the freeway bar up and back then align the hole in the frame brace with the freeway bar's upper mount. Insert the supplied 5/16"-18 x 3/4" buttonhead bolt thru freeway bar mount and into frame brace and secure on the backside with the supplied 5/16" flat washer and 5/16"-18 nylock nut. Make sure freeway bar is aligned properly then fully tighten the 5/16-18" bolt and nut followed by the 3/8"-16 bolts and nuts. Cobra Freeway Bars add style to your motorcycle. They are not designed to withstand a serious impact and may not protect you and/or your motorcvcle in the event of a crash.

