COBRA

23801 E. La Palma Ave., Yorba Linda, CA 92887 Ph. 714.692.8180 Fax. 714.692.5016

tems Supplied >		www.cobrausa-vtwin.c		
– FRONT MUFFLER ASSEMBLY – REAR MUFFLER ASSEMBLY	HA	ARLEY: SUPER GLIDE STREET BOB SUPER GLIDE CUSTOM LOW RIDER	95-10 06-17 05-14 95-09	
nstruction Manual >		6055B	Page 1 of 1	
 Remove the stock mufflers carefully. Save Position the stock clamps with hex head a NOTE: THE MUFFLER WITH THE COBRA LC head pipes until the mounting holes align. Fasten the mufflers using the stock moun the gap, where the mufflers meet the stock Check all clearances and alignments ther the end of the muffler when tightened. Se slip collar the clamps will not tighten the n slots. The slots need to be covered by the necessary). Tighten the mounting bolts to factory speer exhaust system use a liquid based soap de clean water. Note: Avoid abrasive cleaning steel wool pads. Abrasives may breach the 	as shown in Figure 1 DGO WILL ALWAYS BE ting bolts in the same the k heat shields, is sim to tighten the clamps. The Figure 2 . If the mu nufflers properly. Also e clamp band so that cifications. emove all fingerprints tergent, such as dishw methods such as grau	and slide them onto the slip-on <i>THE REAR MUFFLER</i> . Slide the manner as stock but do not tig illar to the gap the stock muffler (NOTE: The muffler clamps sho ffler clamps are slid forward pas o, make sure the clamp spacer i it seals the slots properly. Rotat from all exhaust surfaces. To clear vashing soap applied with a soft on nular or dry cleansers, simple gree	mufflers onto the ghten. Verify that s allotted. uld be flush with it the slots on the s not over the e the clamp if an your black cloth and rinse with	
ORIENT STOCK CLAMPS WITH HEX HEAD AS SHOWN FIGURE 1		CLAMP SHO FLUSH WIT OF MUFFLE DO NOT SLIDE CLAMPS FORWARD PAST SLOTS FIGURE 2	H EDGE R CLAMP SPACER	
	PACKING AND OPTIO	ABOVE MAY VARY FROM ACTU NAL 1¾" QUIET CORES MAY BE LINE AT WWW.COBRAUSA.CON		

